

Introducing the Autobag AB 255 Horizontal Wide Bagger - Setting the pace for large-bag packaging technology.

Capable of bagging at speeds up to 55 bags per minute, this automatic hand load bag sealing machine has been designed to meet the specific requirements of large bag packaging. Capable of running bag widths up to 400mm with a 150mm pass through area, the AB 255 is simple to use, dependable and operationally flexible to deliver maximum packaging productivity.

Utilising the very latest technology, the large interactive AutoTouch™ Control Screen allows operators to recall and quickly set-up packing jobs. The AutoTouch control screen also provides a high capacity memory for job storage as well as a powerful diagnostic help tool to enable operators to rectify machine errors quickly and easily.

The AB 255 Horizontal Wide Bagger provides easy access for hand loading products, providing optimum productivity for applications that require assembly, inspection or product orientation in the bag. Using genuine Autobag pre-made polyethylene bags sized from 100mm x 125mm to 400mm x 660mm, the AB 255 offers a fast and cost-effective packaging solution.



User Benefits

- Quick to set-up, easy to operate, reliable and fast
- Change bag size easily in less than 2 minutes for maximum machine uptime
- Powered Unwind provides positive web control for speed and registration
- Operator friendly AutoTouch™ Control Screen for easy job set-up and control
- Built in diagnostics and help screens for rapid problem solving
- "Replace-n-Repair" system for vital components to ensure minimum downtime due to machine failure
- Combine with Autobag PI 412cw imprinter for complete "Print-n-Pack" in-line product identification and labelling
- With easy access hand load and synchronised product takeaway providing fast operation and product support



BPM
20
30
40
50
55
60
70
80

00095087 007



Standard Features

- Colour AutoTouch™ control screen interface:
 - 25cm screen, offers data storage, help system and diagnostics
 - Performance monitoring e.g. production rates per job, bags-per-minute/hour, etc.
- Powered unwind for positive bag-web control ensures minimum bag movement for accurate positioning and loading and for in-line printing accuracy
- On board memory stores job data ready for recall at a later time
- AutoThread™ automatic bag threading for quick and easy set up and change over
- System handshaking AutoLink™ ports which will allow for a tie-in to APS in-feeds and a wide array of third party equipment
- Simple height adjustment for added operator comfort
- Multiple language choice—English, French, Spanish, German, and Dutch available by making a selection on the touch screen
- Product Support Platform is also a synchronised conveyor providing efficient transition of filled bags from the load area



Modular Valve Pack
 A pneumatic control system designed for productivity, reliability and fast addition or replacement of individual valves.



Modular E-Box.
 Designed to increase uptime, the E-Box is decentralised for easy access to logic and control boards. For maximum uptime, the entire E-Box can be replaced in minutes.

Options

- Trim Seal
- Seal Flatteners
- Mounting kit
- Adjustable In-feed Tray
- Synchronised Bag Deflator
- Range of in-feed funnels
- Spare parts kits

Typical Applications

- Automotive & appliance parts
- Electrical & electronic parts
- Hardware & DIY – bulk pack
- Large plumbing and heating parts & assemblies
- Electrical wiring harnesses and assemblies
- Bulk moulded plastic parts and components
- Instruction manuals & kits



Also available in a vertical configuration the AB 255 is ideal for automatic in-feed applications. The capability to package up to 3.5kgs of bulk product per bag provides solutions for multiple applications.



Technical Specifications

Weight: 177kg	Pass-Through: 117mm to 150mm
Electrical: 110/220 VAC switchable 50/60 Hz	Bag Thickness: 35 to 100 microns
Air Feed: 5 CFM/80 psi of clean, dry air	Bag Sizes: W 100 to 400mm L 125 to 660mm

Dimensions:



Mechanical Features

Stepper motor technology provides high-speed advancement and precise placement of the web of bags maximising productivity.



Powered Unwind, exclusive to Autobag systems, provides web alignment and tension control for consistent film delivery to product load station.



Opposing friction belt design traps the bag web to maintain a constant position for precise product loading and accurate sealing.



Automated Packaging Systems Ltd.
 Enigma Business Park
 Sandy's Road, Malvern
 Worcestershire WR14 1JJ
 Tel: +44 (0) 1684 891 400
 Fax: +44 (0) 1684 891 401
 E-mail: contact@autobag.co.uk